

Distribution



Atlas, a third generation family owned company, has been in the business of manufacturing and distributing spun concrete poles, supplying markets ranging from North America to South America, since 1958

Atlas not only manufactures spun concrete poles with all of its technical requirement but also provides:

- Pre-engineered designs
- Integrated supply chain (S&OP) processes assuring constant supply as well as reduction in lead times
- Custom designs
- Maintenance free poles
- Life time warranty
- Certifications:
 - ISO 9001-2015
 - ASTM (e.g.: A416, C33, C39)
 - IEEE NESC
 - Mexico CFE
 - PCI Committee Report

ATLAS SPUN CONCRETE POLES										
Pole Length (ft)	Above Grade Height	Embedment Depth	Tip Diameter (in)	Bottom Diameter (in)	Nominal Weight (lb)	Concrete Pole Class	Ultimate Transverse Load (lb)	Pole sections		
								Description	Length (ft)	Weight (lb)
29.5	24.5	5	6.5	11.8	1700	C	1200	-	-	-
29.5	24.5	5	6.5	11.8	1750	D	1500	-	-	-
29.5	24.5	5	6.5	11.8	1750	E	2000	-	-	-
29.5	24.5	5	6.5	11.8	1750	F	2400	-	-	-
35.1	29.6	5.5	6.5	12.8	2250	C	1000	-	-	-
35.1	29.6	5.5	6.5	12.8	2250	D	1500	-	-	-
35.1	29.6	5.5	6.5	12.8	2300	E	2000	-	-	-
35.1	29.6	5.5	6.5	12.8	2300	F	2400	-	-	-
39.4	33.5	5.9	6.5	13.6	2700	C	1346	-	-	-
39.4	33.5	5.9	6.5	13.6	2700	D	1500	-	-	-
39.4	33.5	5.9	6.5	13.6	2750	E	2000	-	-	-
39.4	33.5	5.9	6.5	13.6	2750	F	2400	-	-	-
44.9	38.4	6.5	6.5	14.6	3700	E	2000	Tip	19.7	1100
								Base	25.3	2600
44.9	38.4	6.5	6.5	14.6	3700	F	2400	Tip	19.7	1100
								Base	25.3	2600
49.2	42.3	6.9	6.5	15.4	4300	E	2000	Tip	29.5	1900
								Base	19.7	2400
49.2	42.3	6.9	6.5	15.4	4300	F	2400	Tip	19.7	1100
								Base	29.5	3200
49.2	42.3	6.9	8.3	17.1	5550	G	3300	Tip	19.7	1500
								Base	29.5	4050
54.8	47.3	7.5	6.5	16.4	5200	E	2000	Tip	29.5	1850
								Base	25.5	3350
54.8	47.3	7.5	8.3	18.1	6600	G	3000	Tip	29.5	2500
								Base	25.5	4100
59.1	51.2	7.9	6.5	17.1	5900	F	2400	Tip	19.7	1100
								Base	39.4	4800
59.1	51.2	7.9	8.3	18.9	7450	G	3000	Tip	29.5	2500
								Base	29.5	4950
59.1	51.2	7.9	8.3	18.9	7550	H	4000	Tip	29.5	2550
								Base	29.5	5000

